

# **NRC Publications Archive** Archives des publications du CNRC

# The role of the ITTC in the physical modelling of damaged stability in waves

Molyneux, W. D.

For the publisher's version, please access the DOI link below./ Pour consulter la version de l'éditeur, utilisez le lien DOI ci-dessous.

## Publisher's version / Version de l'éditeur:

#### https://doi.org/10.4224/8895291

Laboratory Memorandum (National Research Council of Canada. Institute for Marine Dynamics); no. LM-1996-08, 1996

NRC Publications Archive Record / Notice des Archives des publications du CNRC :

https://nrc-publications.canada.ca/eng/view/object/?id=a428facd-3356-4e97-a9a8-b0ccbb1bcce5 https://publications-cnrc.canada.ca/fra/voir/objet/?id=a428facd-3356-4e97-a9a8-b0ccbb1bcce5

Access and use of this website and the material on it are subject to the Terms and Conditions set forth at https://nrc-publications.canada.ca/eng/copyright

READ THESE TERMS AND CONDITIONS CAREFULLY BEFORE USING THIS WEBSITE.

L'accès à ce site Web et l'utilisation de son contenu sont assujettis aux conditions présentées dans le site https://publications-cnrc.canada.ca/fra/droits LISEZ CES CONDITIONS ATTENTIVEMENT AVANT D'UTILISER CE SITE WEB.

Questions? Contact the NRC Publications Archive team at PublicationsArchive-ArchivesPublications@nrc-cnrc.gc.ca. If you wish to email the authors directly, please see the first page of the publication for their contact information.

Vous avez des questions? Nous pouvons vous aider. Pour communiquer directement avec un auteur, consultez la première page de la revue dans laquelle son article a été publié afin de trouver ses coordonnées. Si vous n'arrivez pas à les repérer, communiquez avec nous à PublicationsArchive-ArchivesPublications@nrc-cnrc.gc.ca.





National Research Conseil national de recherches Canada



National Research Council Canada

Institute for

Conseil national de recherches Canada Institut des Ocean Technology technologies océaniques

# Laboratory Memorandum

LM-1996-08

# The Role of the ITTC in the Physical Modelling of Damaged Stability in Waves

David Molyneux

August 1996



# DOCUMENTATION PAGE

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

REPORT NUMBER LM-1996-08		NRC REPORT NUMBER	DATE August 1	996	
REPORT SECURITY CLASSIFICATION Unclassified			DISTRIBUTION Unlimited		
TITLE					
THE ROLE OF THE ITTC IN THE PHYSICAL MODELLING OF DAMAGED STABILITY IN WAVES					
AUTHOR(S)					
David Molyneux					
CORPORATE AUTHOR(S)/PERFORMING AGENCY(S)					
Institute for Marine Dynamics National Research Council Canada					
PUBLICATION					
SPONSORING AGENCY(S)					
Institute for Marine Dynamics National Research Council Canada					
IMD PROJECT NUMBER 663			NRC FILE NUMBER		
KEY WORDS model testing, dam	aged sta	bility	PAGES 8	FIGS.	TABLES
SUMMARY					
This report was prepared in response to a workshop on stability work relevant to the ITTC, to be held on September 18th, 1996. It describes IMD's proposals for the role of the ITTC in model testing damaged ships.					
ADDRESS National Research Council Institute for Marine Dynamics P. O. Box 12093, Station 'A' St. John's, Newfoundland, Canada A1B 3T5					

#### The Role of the ITTC in the Physical Modelling of Damaged Stability In Waves

David Molyneux Senior Research Officer

Institute for Marine Dynamics, National Research Council of Canada

#### Background

The recent tragedies related to RO-RO ferry capsize have prompted a flurry of activity around the world in the area of physical modelling of the capsize of flooded ships in waves (see bibliography). The techniques used for this work have all followed the path set by Bird & Browne (1973). The objectives of the model tests have been;

a) to understand the physical phenomena which limit survivability of ships after damage

b) to translate these physical phenomena into regulations

or more recently

c) to validate regulations after they have been proposed.

The latter of these three categories is the one which should be most worrying to the members of the ITTC. The IMO set up a Panel of Experts to review passenger ship safety after the sinking of the 'M. V. Estonia'. This panel recommended a procedure for model testing damaged ships as an alternative to prescriptive rules. The procedure was a genuine attempt to address the fact that simplistic approaches do not always address the specifics of a particular case, and the recommendations cannot be seriously criticized on the basis of the current state of the art. However, the ITTC must address the sensitivity of the results of experiments to the simplifications assumed for the convenience of the model testers.

# Proposals for ITTC Activity in Physical Modelling of Damage Stability in Waves

So far, there are relatively few data sets for studying the damage stability of ships in waves, and with one exception, they have focused on RO-RO ferries. The tests have modelled a relatively small range of ship proportions, but there has been a lot of attention paid to the details of the design, such as the use of bulkheads to subdivide the car deck, and features such as external sponsons

and air bags. Most experiments are reported in terms of limiting wave height for survivability, for a given residual freeboard, and a stability parameter. To date, the most popular choice has been the metacentric height of the flooded ship.

In some cases, results have been presented in non-dimensional form. Residual freeboard and significant waveheight have been combined into a single parameter and several proposals have been made for non-dimensional metacentric height;

Dand (1991)

 $\frac{10 \times GM_{f} \times B \times C_{b}}{T^{2}}$ 

Spouge (1994)

 $\frac{\text{D x GM}_{\text{f}}}{1.025 \text{ x L x B}^3}$ 

Vassalos (1996)

 $\frac{D \times GM_f}{T^2} \qquad \frac{GM_f \times T \times C_b}{L \times B^2}$ 

Where

GM<sub>f</sub> is the flooded metacentric height, m

D is the displacement of the flooded ship, tonnes

B is the beam of the ship, m

C<sub>b</sub> is the block coefficient of the flooded ship

L is the length of the ship, m

T is the draft of the flooded ship, m

However, as Vassalos et al (1996) point out, none of these parameters recognize the influence of the structural arrangement on stability. This leads to the suggestion (Vassalos et al, 1996) that other parameters such as maximum GZ lever are more important.

The work of the ITTC Stability Committee should include developing standard procedures for test programs and a set of variables that must be reported for the ship model and the wave parameters. These parameters should include the stability factors for the damaged model, the geometry of the hull and the compartments after flooding, the wave spectra and the parameters to be measured on the model. This will allow the maximum benefit to be derived from

all experiments and also enable the results of the experiments to be used in the validation of numerical models of the process. A preliminary list variables is attached in Annex A.

The other major research item to be addressed is the sensitivity of the results to factors such as the permeability of the hull and the cargo deck. The flow of water onto the deck and around cargo (such as cars and trucks) during flooding is not well understood in a physical sense, and a series of experiments to observe the influence of cargo on the process is an essential step in convincing ship owners and regulators that the results of reduced scale experiments are valid. Schindler & Velschou (1994) carried out one set of tests with cargo on the vehicle deck and this showed that the waveheight required to capsize the ship was not significantly different from the empty deck case. However, the time to capsize, which is an important parameter for evacuating the damaged ship, was not reported. Similar arguments can be made for the permeability of under-deck spaces such as engine rooms.

Spouge (1985) proposed the concept of transient asymetrical flooding, or the concept of time dependent changes in ship stability during flooding, to account for the observed behaviour of the 'European Gateway' when she capsized. This theory has not been validated experimentally, since the all hulls used in the experiments to date did not study internal flooding from one compartment to another. It is important that the limits of classical hydrostatic assumptions are established.

#### Conclusion

In conclusion, I have tried to focus on issues related to carrying out experiments, and avoid issues related to the development of regulations or ship specific issues (such as the specific subdivision arrangements). It is the responsibility of the ITTC membership to provide accurate and reliable methods for testing damaged ships, which reflect the best scientific principles. ITTC members have done a good job in providing information to support the regulators, but now is the time to take stock of the progress in the field, and recommend procedures that will ensure we advance our understanding in this important area of ship stability research.

#### Bibliography

V. Aanesland, 'Limiting Waveheights for Damaged RO-RO/Passenger Vessels', International Conference on the Safety of RO-RO Passenger Vessels, RINA, June 1996

H. Bird & R. P. Browne, 'Damage Stability Model Experiments', Trans. RINA 1973.

A. Damsgaard & M. Schindler, 'Model Tests for Determining Water Ingress and Accumulation', International Conference on the Safety of RO-RO Passenger Vessels, RINA, June 1996

I. W. Dand, 'Hydrodynamic Aspects of the Sinking of Herald of Free Enterprise', Trans. RINA, 1989.

I. W. Dand, 'Experiments with a Floodable Model of a RO-RO Passenger Ferry', International Conference on RO-RO Safety and Vulnerability, The Way Ahead, RINA, London, April 17-19, 1991

I. W. Dand, ' Factors Affecting the Capsize of Damaged RO-RO Vessels in Waves', Symposium on RO-RO Ships' Survivability, RINA, London, 25 November 1994

S. Murashige, 'Tests of a Damaged Ro-Ro Ferry in Waves', Ship Research Institute, Ministry of Transport, Japan, October 24, 1995.

M. Nattero and P. Blume, 'Survivability Tests with a Damaged RO-RO Passenger Vessel According to the New IMO Regulations and Further Activities Planned by Confirmata and HSVA', RO-RO 96, Lubeck, April 1996

F. Pucill & S. Velschou, 'RO-RO Passenger Ferry Safety Studies - Model Tests of a Typical Ferry' International Symposium on the Safety of RO-RO Passenger Ships, RINA, London, April 26-27, 1990.

M. Schindler & S. Velschou, 'RO-RO Passenger Ferry Damage Stability Studies- A Continuation of Model Tests for a Typical Ferry', RO-RO 94 Gothenberg, 26-28 April 1994

M. Schindler, 'RO-RO Passenger Ferry Damage Stability Studies- A Continuation of Model Tests for a Typical Ferry', Symposium on RO-RO Ships' Survivability, RINA, London, 25 November 1994

J. Spouge, 'The Technical Investigation of the Sinking of the RO-RO Ferry European Gateway', Trans. RINA, 1985.

J. Spouge, 'A Technique to Predict the Capsize of a Damaged RO-RO Ferry', Symposium on RO-RO Ships' Survivability, RINA, London, 25 November 1994

J. Stubbs, D. Molyneux, M. Koniecki, T. Pierce and J. Rousseau, 'Flooding Protection of RO-RO Ferries', Spring Meetings, RINA, April 1996

D, Vaasalos, M. Pawlowlski and O. Turan, 'Criteria for Survival in Damaged Condition', International Conference on the Safety of RO-RO Passenger Vessels, RINA, June 1996

#### ANNEX A

#### List of Variables to be Reported During Damage Stability Experiments

#### **Hull Parameters**

Intact (upright) hydrostatics (displacement, GM, draft, trim, depth to car deck) Damaged hydrostatics (flooded displacement, flooded GM, GZ vs heel angle) Residual freeboard in calm water Volume of flooding and location Midship section and car deck plan showing extent of damage Location of any special features such as bulkheads, freeing ports or casings

#### **Wave Parameters**

Significant waveheight, peak period, energy spectrum, Model orientation relative to wave direction

#### **Experiment Parameters**

Time histories (minimum sampling rate of 20Hz model scale)

Roll, heave, sway, pitch, surge and yaw Waveheight close to location of model, Water level on car deck (at a minimum of 10 locations), Relative motion at damage location, Model speed, relative to wave direction, Time to capsize

## ANNEX B

# Presentation to ITTC Stability Workshop

Friday 20 September

į



## Background

- Model tests on damaged stability have been carried out to
  - » understand physics of problem
  - \* translate physics into regulation
  - » validate regulations (or proposed regulations)

## IMO Panel of Experts Proposal

- Fall out from Estonia disaster
- Model tests as an alternative to prescriptive rules
- Allows for physical representation of hull and special features (e.g. bulkheads)

3

6

Current state of the art

### Issues to be Addressed by Physical Modeling

2

A)

6)

- Sensitivity of parameters not understood
  small number of data sets
  - small range of ship proportions
    choice of stability parameters
- Influence of vehicles on car deck
- Influence of transient effects during flooding

## Role of ITTC in Modeling Damaged Stability

- Standardize on test methods and data presentation
- \* acceptance by user community
- \* easier comparison of experiment results
- \* easier integration with numerical models
- Address modeling of
- \* vehicles on car deck and permeability of
- spaces under bulkhead deck
- » stability during flooding

# Conclusions

- Experiment results must be to highest technical standard
- Address knowledge gaps through further research